

View Online at <https://aerobasegroup.com/nsn/5315-00-009-4760>

First End Style:

Slotted

Overall Length:

2.870 inches

Diameter:

Between 0.2492 inches and 0.2497 inches

Effective Length:

2.250 inches

Undercut Diameter:

0.195 inches

Undercut Width:

0.070 inches

Undercut Radius:

0.035 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.077 inches and 0.082 inches

Second Hole Diameter:

Between 0.077 inches and 0.082 inches

Distance From Centerline Of Hole To End Of Pin:

0.138 inches

Center To Center Distance Between Holes:

2.594 inches

First End Slot Width:

0.050 inches

First End Slot Depth:

0.094 inches

Second End Relationship With First End:

Identical

Hardness Rating:

38.0 rockwell c and 44.0 rockwell c

First End Location:

Both ends

Surface Finish:

63.0 microinches

Special Features:

1/4-28 unf-2a threaded to grooves on both ends; holes drilled 90 degrees to slot both ends

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, d4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.