

View Online at <https://aerobasegroup.com/nsn/5315-00-024-7713>

First End Style:

Chamfered

Head Style:

Flat

Diameter:

Between 0.3116 inches and 0.3120 inches

Effective Length:

Between 0.6378 inches and 0.6398 inches

Undercut Diameter:

Between 0.300 inches and 0.305 inches

Under Head Length:

Between 0.829 inches and 0.859 inches

Undercut Width:

Between 0.040 inches and 0.060 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.0625 inches and 0.0629 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.169 inches and 0.179 inches

First End Taper Length:

0.062 inches

Grip Length:

0.671 inches

Features Provided:

Casehardened

Hardness Rating:

89.0 rockwell superficial 15-n

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

0.875 inches

Height:

Between 0.047 inches and 0.077 inches

Material:

Steel

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-c-16232 type 1 military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-16232 spec.