

View Online at <https://aerobasegroup.com/nsn/5315-00-024-7713>

**First End Style:**

Chamfered

**Head Style:**

Flat

**Diameter:**

Between 0.3116 inches and 0.3120 inches

**Effective Length:**

Between 0.6378 inches and 0.6398 inches

**Undercut Diameter:**

Between 0.300 inches and 0.305 inches

**Under Head Length:**

Between 0.829 inches and 0.859 inches

**Undercut Width:**

Between 0.040 inches and 0.060 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.0625 inches and 0.0629 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.169 inches and 0.179 inches

**First End Taper Length:**

0.062 inches

**Grip Length:**

0.671 inches

**Features Provided:**

Casehardened

**Hardness Rating:**

89.0 rockwell superficial 15-n

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

0.875 inches

**Height:**

Between 0.047 inches and 0.077 inches

**Material:**

Steel

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Mil-c-16232 type 1 military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-16232 spec.