NSN 5315-00-026-6620

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-026-6620 First End Style: Chamfered **Overall Length:** Between 1.115 inches and 1.135 inches Diameter: Between 0.4990 inches and 0.4995 inches **Effective Length:** Between 0.875 inches and 0.880 inches **Undercut Diameter:** Between 0.472 inches and 0.476 inches **Undercut Width:** Between 0.039 inches and 0.042 inches **Second Undercut Width:** Between 0.039 inches and 0.042 inches First End Taper Length: Between 0.005 inches and 0.025 inches Second End Relationship With First End: Identical **Hardness Rating:** 55.0 rockwell c and 60.0 rockwell c **First End Location:** Both ends First End Taper Angle: Between 40.0 degrees and 50.0 degrees **Surface Finish:** 32.0 microinches outside diameter Material: Steel comp 1020 **Material Specification:** Sae assn standard single material response **Surface Treatment:** Phosphate zinc or phosphate manganese **Surface Treatment Specification:** Mil-c-16232 type 2 military specification 1st treatment response or mil-c-16232 type 1 military specification 2nd treatment response **Style Designator:** Groove Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5315-00-026-6620

Headless Grooved Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-c-16232 spec.