

View Online at <https://aerobasegroup.com/nsn/5315-00-026-6621>

**First End Style:**

Chamfered

**Overall Length:**

Between 0.990 inches and 1.010 inches

**Diameter:**

Between 0.3740 inches and 0.3745 inches

**Effective Length:**

Between 0.750 inches and 0.755 inches

**Undercut Diameter:**

Between 0.350 inches and 0.354 inches

**Undercut Width:**

Between 0.028 inches and 0.030 inches

**Second Undercut Width:**

Between 0.028 inches and 0.030 inches

**First End Taper Length:**

Between 0.005 inches and 0.025 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

55.0 rockwell c and 60.0 rockwell c

**First End Location:**

Both ends

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Surface Finish:**

32.0 microinches outside diameter

**Material:**

Steel comp 1020

**Material Specification:**

Sae assn standard single material response

**Surface Treatment:**

Phosphate zinc or phosphate manganese

**Surface Treatment Specification:**

Mil-c-16232 type 2 military specification 1st treatment response or mil-c-16232 type 1 military specification 2nd treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-c-16232 spec.