

View Online at <https://aerobasegroup.com/nsn/5315-00-034-4840>

**Head Style:**

Knurled no. 1

**Chamfer Length:**

0.500 inches

**Diameter:**

Between 0.994 inches and 0.996 inches

**Under Head Length:**

2.812 inches

**Features Provided:**

Casehardened

**Hardness Rating:**

89.5 rockwell superficial 15-n and 91.5 rockwell superficial 15-n

**Pin Chamfer Angle:**

60.0 degrees

**Pin Head Diameter:**

2.000 inches

**Special Features:**

Retaining groove cut into pin shaft around length, 0.1275 in. Deep

**Height:**

0.375 inches

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1024 or steel comp 1025 or steel comp 1109 or steel comp 1110 or steel comp 1111 or steel comp 1112 or steel comp 1113 or steel comp 1114 or steel comp 1115 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1120

**Material Specification:**

Qq-s-633 federal specification all material responses or mil-s-13048 military specification all material responses

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type ii, class 3 federal specification all treatment responses or qq-z-325, type ii, class 3 federal specification all treatment responses

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-13048 spec.