

View Online at <https://aerobasegroup.com/nsn/5315-00-034-6244>

**Head Diameter:**

Between 0.350 inches and 0.450 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

Between 1.100 inches and 1.125 inches

**Detent Quantity:**

4

**Actuation Method:**

Push button

**Grip Length:**

Between 2.500 inches and 2.520 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shoulder To Head End Distance:**

0.935 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.360 inches and 0.460 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.