

View Online at <https://aerobasegroup.com/nsn/5315-00-044-3448>

**Shank Diameter:**

Between 0.4935 inches and 0.4970 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.600 inches and 3.620 inches

**Actuation Type:**

Push

**Features Provided:**

Lock open feature

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shoulder To Head End Distance:**

1.820 inches

**Pin Center To Handle End Distance:**

2.000 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.530 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

80205-nas1338 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.