

View Online at <https://aerobasegroup.com/nsn/5315-00-045-4556>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Shank Length:**

Between 0.610 inches and 0.625 inches

**Shoulder Diameter:**

Between 0.735 inches and 0.750 inches

**Shank Diameter:**

Between 0.360 inches and 0.375 inches

**Overall Length:**

2.687 inches

**First End Taper Length:**

0.062 inches

**Second End Taper Length:**

0.062 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

28.0 rockwell c and 33.0 rockwell c

**Second Shank Diameter:**

Between 0.360 inches and 0.375 inches

**First End Location:**

Both ends

**First End Taper Angle:**

30.0 degrees

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

Between 0.610 inches and 0.625 inches

**Special Features:**

0.187 in. Min 0.192 in. Maximum diameter hole drilled 0.312 in. From end of longer shank

**Material:**

Steel comp 4130 and steel comp 5130 or steel comp 8630

**Surface Treatment:**

Phosphate

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0