

View Online at <https://aerobasegroup.com/nsn/5315-00-046-3851>

First End Style:

Chamfered

Head Style:

Flat chamfer

Under Head Length:

2.090 inches

First Step Diameter:

Between 0.3115 inches and 0.3119 inches

First Step Length:

Between 1.860 inches and 1.880 inches

Second Step Diameter:

Between 0.302 inches and 0.307 inches

Second Step Length:

Between 0.210 inches and 0.230 inches

First End Taper Length:

Between 0.010 inches and 0.020 inches

Hardness Rating:

39.0 rockwell c and 49.0 rockwell c

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

0.625 inches

Surface Finish:

32.0 microinches shoulder end

Special Features:

0.065 in. Min 0.072 in. Maximum diameter hole drilled through second step on center line 0.130 in. Min 0.140 in. Maximum lg from chamfered end, solid film lubricant/molykote/ on shoulder

Height:

0.080 inches

Material:

Steel comp 420

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074 cl2 grb military specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-c-26074 spec.