

View Online at <https://aerobasegroup.com/nsn/5315-00-046-3865>

**First End Style:**

Chamfered

**Head Style:**

Flat

**Under Head Length:**

0.740 inches

**First Step Diameter:**

Between 0.3115 inches and 0.3119 inches

**First Step Length:**

Between 0.595 inches and 0.605 inches

**Second Step Diameter:**

Between 0.245 inches and 0.255 inches

**Second Step Length:**

Between 0.135 inches and 0.145 inches

**First End Taper Length:**

Between 0.015 inches and 0.025 inches

**Hardness Rating:**

49.0 rockwell c and 52.0 rockwell c

**First End Taper Angle:**

15.0 degrees

**Pin Head Diameter:**

0.375 inches

**Surface Finish:**

32.0 microinches shoulder end

**Special Features:**

Solid film lubricant/molykote/ on shoulder

**Height:**

0.060 inches

**Material:**

Steel comp 420

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074 cl2 grb military specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-c-26074 spec.