## NSN 5315-00-050-1384

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-050-1384 First End Style: Chamfered Second End Style: Slotted **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.173 inches **Shank Length:** 0.203 inches **Shoulder Diameter:** Between 0.137 inches and 0.142 inches **Shank Diameter:** 0.112 inches **Overall Length:** 0.609 inches **Undercut Diameter:** 0.078 inches **Undercut Width:** 0.031 inches **Internal Drive Style:** Slot **Second End Slot Width:** 0.039 inches First End Taper Length: 0.030 inches **Second End Slot Depth:** 0.058 inches Second End Relationship With First End: Not identical **Thread Size:** 0.112 inches First End Location: Chamfered end First End Taper Angle: 45.0 degrees **Special Features:** 1st end thd; 2nd end spherical radius

Material:

Stainless steel

## NSN 5315-00-050-1384

Headless Shoulder Pin - Page 2 of 2

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.



Material Specification:
Qq-s-763, cl 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, fin. E300 military specification single treatment response
Style Designator:
Undercut
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: