

View Online at <https://aerobasegroup.com/nsn/5315-00-051-1411>

**Head Diameter:**

Between 0.600 inches and 0.620 inches

**Shank Diameter:**

Between 0.187 inches and 0.189 inches

**Ring Handle Diameter:**

1.060 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

8wsd: tarawa class lha; ta-4j aircraft; helicopter, carrier based asw, sh-60f; fighting vehicle systems, bradley (bfvs); aircraft, galaxy c-5; arleigh burke class ddg; support equipment, f-4 aircraft; support equipment, f-16 aircraft; aircraft, f-16

**Grip Length:**

Between 1.000 inches and 1.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c

**Shoulder To Head End Distance:**

0.730 inches

**Criticality Code Justification:**

Feat

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.230 inches and 0.260 inches

**Special Features:**

Weapon system essential

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0