

View Online at <https://aerobasegroup.com/nsn/5315-00-051-1411>

Head Diameter:

Between 0.600 inches and 0.620 inches

Shank Diameter:

Between 0.187 inches and 0.189 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

8wsd: tarawa class lha; ta-4j aircraft; helicopter, carrier based asw, sh-60f; fighting vehicle systems, bradley (bfvs); aircraft, galaxy c-5; arleigh burke class ddg; support equipment, f-4 aircraft; support equipment, f-16 aircraft; aircraft, f-16

Grip Length:

Between 1.000 inches and 1.020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c

Shoulder To Head End Distance:

0.730 inches

Criticality Code Justification:

Feat

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.230 inches and 0.260 inches

Special Features:

Weapon system essential

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0