## NSN 5315-00-051-4108

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-051-4108 **Head Diameter:** Between 0.600 inches and 0.800 inches **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Ring Handle Diameter:** 1.160 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.100 inches and 2.120 inches **Actuation Type:** Push Hardness Rating: 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.140 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate shank **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-00-051-4108

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.