

View Online at <https://aerobasegroup.com/nsn/5315-00-052-6442>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Drilled through center

**First Hole Diameter:**

Between 0.374 inches and 0.377 inches

**Pinlength:**

2.460 inches

**Pindiameter:**

Between 0.4980 inches and 0.4990 inches

**First End Taper Length:**

0.030 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

40.0 rockwell c and 46.0 rockwell c

**First End Taper Angle:**

Between 43.0 degrees and 47.0 degrees

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Cva1-680378, fscm 80378 mfr ref single treatment response

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0