

View Online at <https://aerobasegroup.com/nsn/5315-00-052-8811>

Handle Length:

Between 1.750 inches and 2.000 inches

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.700 inches and 1.720 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shoulder To Head End Distance:

1.550 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758hmdcl1cjdbmil-s-6758 military specification single material response spindle or mil-t-6736 military specification 1st material response spindle or mil-t-6735 military specification 2nd material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

Style Designator:

T handle

Specification Data:

80205-nas1334 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758hmdcl1cjdbmil-s-6758 spec.