

View Online at <https://aerobasegroup.com/nsn/5315-00-059-8197>

First End Style:

Chamfered

Second End Style:

Slotted

Inside Diameter:

0.261 inches

Pinlength:

2.000 inches

Pindiameter:

Between 0.9980 inches and 0.9990 inches

Second End Slot Width:

Between 0.150 inches and 0.155 inches

First End Taper Length:

0.030 inches

Second End Slot Depth:

Between 0.200 inches and 0.210 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

First End Taper Angle:

Between 43.0 degrees and 47.0 degrees

Special Features:

Slotted end chamfered 0.060 in. Lg by 43.0 in. Min, 47.0 in. Maximum degrees

Material:

Steel

Material Specification:

Cva1-585 cond c-1 mfr ref single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Cva5-2 fscm 16615 mfr ref single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0