

View Online at <https://aerobasegroup.com/nsn/5315-00-060-6987>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Chamfer Length:**

0.078 inches

**Diameter:**

Between 0.620 inches and 0.622 inches

**Under Head Length:**

Between 2.006 inches and 2.026 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.131 inches and 0.151 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.165 inches

**End Application:**

W/s: cargo system, 463l; tank, abrams m-1; tank, combat, ft, 120mm gun (m1a1); carrier, pers m-113a1, m-113a2, m-113a3

**Hardness Rating:**

26.05 rockwell c and 32.0 rockwell c

**Pin Chamfer Angle:**

15.0 degrees

**Shear Strength:**

46020 double pound

**Pin Head Diameter:**

0.750 inches

**Height:**

0.093 inches

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6300 military specification 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.