NSN 5315-00-062-7251

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-062-7251 **Head Style:** Pan no. 2 (r1 not required in item description) **Chamfer Length:** 0.062 inches Diameter: Between 0.122 inches and 0.124 inches **Under Head Length:** Between 1.897 inches and 1.917 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.060 inches and 0.080 inches Distance From Centerline Of Hole To End Of Pin: 0.091 inches **Hardness Rating:** 26.5 rockwell c and 32.0 rockwell c Pin Chamfer Angle: Between 14.5 degrees and 15.5 degrees **Shear Strength:** 1840 double pound Pin Head Diameter: Between 0.234 inches and 0.266 inches **Special Features:** The shank end may have either a chamfer or radius at the option of the vendor Height: Between 0.030 inches and 0.062 inches Material: Steel comp 4037 or steel comp 4130 or steel comp 8630 **Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Style Designator:**

Demilitarization:

Unit Of Measure:

Straight Shelf Life:

N/a

No

NSN 5315-00-062-7251

Headed Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.