

View Online at <https://aerobasegroup.com/nsn/5315-00-072-4166>

First End Style:

Chamfered

Second End Style:

Pointed

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.620 inches

Shank Length:

0.620 inches

Shoulder Width Across Flats:

0.375 inches

Shank Diameter:

Between 0.184 inches and 0.186 inches

Overall Length:

1.960 inches

First End Taper Length:

0.030 inches

Second End Taper Length:

0.160 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

40.0 rockwell c and 47.0 rockwell c

Thread Size:

0.190 inches

Second Shank Diameter:

Between 0.184 inches and 0.186 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Surface Finish:

32.0 microinches large shank

Second End Taper Angle:

60.0 degrees

Second Shank Length:

0.620 inches

Special Features:

Tapered end location

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Mil-c-23422 cl 2 type 2 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-23422 spec.