## NSN 5315-00-073-6750

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-073-6750 First End Style: Radius **Head Style:** Double chamfer **Under Head Length:** Between 1.130 inches and 1.134 inches First Step Diameter: Between 0.745 inches and 0.748 inches First Step Length: Between 0.372 inches and 0.375 inches **Second Step Diameter:** 0.756 inches **Second Step Length:** Between 0.495 inches and 0.498 inches First End Corner Radius: Between 0.003 inches and 0.015 inches Pin Head Diameter: 0.875 inches **Surface Finish:** 125.0 microinches **Special Features:** Drilled hole through shank 0.092 in. Min 0.097 in. Maximum diameter 0.140 in. Min 0.143 in. Maximum from shank end Height: 0.119 inches Material: Steel comp 4130 **Material Specification:** Mil-s-18729 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl1 federal specification single treatment response **Style Designator:** Shoulder Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A212a0

## NSN 5315-00-073-6750

Headed Shoulder Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-18729 spec.