

View Online at <https://aerobasegroup.com/nsn/5315-00-075-3010>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Chamfer Length:**

Between 0.062 inches and 0.094 inches

**Diameter:**

Between 0.745 inches and 0.747 inches

**Under Head Length:**

3.516 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.131 inches and 0.151 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.165 inches

**Hardness Rating:**

26.5 rockwell c and 32.0 rockwell c

**Pin Chamfer Angle:**

Between 14.5 degrees and 15.5 degrees

**Shear Strength:**

66280 double pound

**Pin Head Diameter:**

Between 0.859 inches and 0.891 inches

**Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

**Height:**

Between 0.077 inches and 0.109 inches

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:**

Mil-s-8695 military specification 1st material response shank or mil-s-6785 military specification 2nd material response shank or mil-s-6050 military specification 3rd material response shank

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-8695 spec.