NSN 5315-00-075-3688

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-075-3688 First End Style: Chamfered **Head Style:** Flat **Under Head Length:** 1.761 inches First Step Diameter: Between 0.600 inches and 0.601 inches First Step Length: 0.356 inches **Second Step Diameter:** Between 0.436 inches and 0.438 inches Second Step Length: 0.609 inches Third Step Diameter: 0.187 inches Third Step Length: 0.187 inches **Internal Drive Style:** Slot First End Taper Length: 0.031 inches **Hardness Rating:** 39.0 rockwell c and 42.0 rockwell c First End Taper Angle: 45.0 degrees Pin Head Diameter: 0.670 inches Surface Finish: 125.0 microinches **Special Features:** One drilled hole located on third step 0.095 in. Diameter 0.093 in. From end 0.050 inches Material:

Height:

Steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-5000 military specification all material responses

Surface Treatment:

Chromium

Surface Treatment Specification:

Gss 8.250m cl 2 fscm 26512 mfr ref single treatment response

NSN 5315-00-075-3688

Headed Shoulder Pin - Page 2 of 2



Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Mil-s-5000 spec.