## NSN 5315-00-075-3688

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-075-3688

First End Style
First End Style: Chamfered
Head Style: Flat
Under Head Length:
1.761 inches
First Step Diameter: Between 0.600 inches and 0.601 inches
First Step Length:
0.356 inches
Second Step Diameter: Between 0.436 inches and 0.438 inches
Second Step Length:
0.609 inches
Third Step Diameter:
0.187 inches
Third Step Length:
0.187 inches
Internal Drive Style:
Slot
First End Taper Length:
0.031 inches
Hardness Rating:
39.0 rockwell c and 42.0 rockwell c
First End Taper Angle:
45.0 degrees
Pin Head Diameter:
0.670 inches
Surface Finish:
125.0 microinches
Special Features:
One drilled hole located on third step 0.095 in. Diameter 0.093 in. From end
Height:
0.050 inches
Material:
Steel comp e4340 or steel comp 4340
Material Specification:
Mil-s-5000 military specification all material responses
Surface Treatment:
Chromium
Surface Treatment Specification:

Gss 8.250m cl 2 fscm 26512 mfr ref single treatment response

## NSN 5315-00-075-3688

Headed Shoulder Pin - Page 2 of 2

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-s-5000 spec.

