View Online at https://aerobasegroup.com/nsn/5315-00-075-3786

First End Style:

Square

Second End Style:

Square internally threaded

Thread Class:

3a

Thread Direction:

Right-hand

First Step Length:

0.187 inches

Second Step Diameter:

Between 0.6145 inches and 0.6155 inches

Second Step Length:

Between 1.880 inches and 1.890 inches

Third Step Diameter:

Between 0.4360 inches and 0.4370 inches

Third Step Length:

0.593 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.104 inches and 0.111 inches

Distance From Centerline Of Hole To End Of Pin:

0.180 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.4375 inches

First End Location:

Shoulder end

Special Features:

Lubrication fitting ms15001-4 is attached by mounting in 0.250-28unf-2b class fit by 0.125 inches depth drilled threaded hole on large shoulder end; on longitudinal center line drilled 0.062 inches min 0.065 inches maximum diameter through one wall only; g41-20 thread relief undercut on first shank 0.359 inches min 0.369 inches maximum diameter

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.