NSN 5315-00-080-1942

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-080-1942

Head Style:

Pan no. 2 (r1 not required in item description)

Chamfer Length:

0.062 inches

Diameter:

Between 0.122 inches and 0.124 inches

Under Head Length:

Between 1.147 inches and 1.167 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.060 inches and 0.080 inches

Distance From Centerline Of Hole To End Of Pin:

0.091 inches

Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

Shear Strength:

1840 double pound

Pin Head Diameter:

Between 0.234 inches and 0.266 inches

Special Features:

The shank end maximum have either a chamfer or radius at the option of the vendor

Height:

Between 0.030 inches and 0.062 inches

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification

3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Straight

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5315-00-080-1942

Headed Straight Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

