

View Online at <https://aerobasegroup.com/nsn/5315-00-089-4062>

**Head Diameter:**

Between 0.350 inches and 0.460 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 3.750 inches and 4.250 inches

**Grip Length:**

Between 0.300 inches and 0.320 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shoulder To Head End Distance:**

0.935 inches

**Pin Attachment Type:**

Chain lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.360 inches and 0.410 inches

**Special Features:**

Painted red mil-f-14072 finish p313

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.