

View Online at <https://aerobasegroup.com/nsn/5315-00-089-4062>

Head Diameter:

Between 0.350 inches and 0.460 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Lanyard Length:

Between 3.750 inches and 4.250 inches

Grip Length:

Between 0.300 inches and 0.320 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shoulder To Head End Distance:

0.935 inches

Pin Attachment Type:

Chain lanyard w/terminations

Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

Special Features:

Painted red mil-f-14072 finish p313

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.