

View Online at <https://aerobasegroup.com/nsn/5315-00-089-4943>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Pinlength:**

Between 0.865 inches and 0.885 inches

**Pindiameter:**

Between 0.1571 inches and 0.1573 inches

**First End Taper Length:**

Between 0.016 inches and 0.047 inches

**Second End Taper Length:**

0.036 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**First End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Second End Taper Angle:**

Between 4.0 degrees and 12.0 degrees

**Special Features:**

Small chamfered end may have 0.016 in. Min 0.047 in. Maximum radius in lieu of chamfer

**Material:**

Steel comp 410 or steel comp 416

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 2 or 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0