

View Online at <https://aerobasegroup.com/nsn/5315-00-089-9307>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Shank Length:**

0.250 inches

**Shoulder Diameter:**

0.310 inches

**Shank Diameter:**

Between 0.250 inches and 0.252 inches

**Undercut Diameter:**

Between 0.210 inches and 0.212 inches

**Undercut Width:**

0.218 inches

**Second Undercut Width:**

0.620 inches

**Second End Slot Width:**

0.019 inches

**First End Taper Length:**

0.030 inches

**Second End Slot Depth:**

0.338 inches

**Second End Relationship With First End:**

Not identical

**Second Shank Diameter:**

Between 0.250 inches and 0.252 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.343 inches

**Material:**

Copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 462

**Material Specification:**

Qq-b-637 1/2 hard federal specification all material responses

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

101469 fscm 07639 mfr ref single treatment response

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0