

View Online at <https://aerobasegroup.com/nsn/5315-00-100-8830>

**Shank Diameter:**

Between 0.1870 inches and 0.1885 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 3.500 inches and 4.500 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 0.900 inches and 0.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shear Strength:**

5150 double pounds per square inch

**Shoulder To Head End Distance:**

0.830 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.230 inches and 0.260 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-w-423, comp 302, cond b federal specification single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spring

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.