

View Online at <https://aerobasegroup.com/nsn/5315-00-101-8581>

Head Diameter:

Between 0.485 inches and 0.515 inches

Shank Diameter:

Between 0.370 inches and 0.373 inches

Ring Handle Diameter:

1.187 inches

Detent Quantity:

2

Lanyard Length:

12.000 inches

Grip Length:

Between 3.000 inches and 3.020 inches

Actuation Type:

Pull and push

Hardness Rating:

58.0 rockwell c and 62.0 rockwell c detent

Shoulder To Head End Distance:

0.562 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.390 inches

Material:

Steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp 1146 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp b1111 or steel comp b1112 or steel comp b1113 or steel comp 12114 or steel comp 4130 head

Material Specification:

Qq-w-470 federal specification single material response spring

Surface Treatment:

Passivate detent

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spring

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec