

View Online at <https://aerobasegroup.com/nsn/5315-00-110-5577>

**First End Style:**

Chamfered

**Shank Length:**

0.343 inches

**Shoulder Diameter:**

Between 0.308 inches and 0.312 inches

**Shank Diameter:**

Between 0.182 inches and 0.187 inches

**Overall Length:**

7.620 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.069 inches and 0.074 inches

**Second Hole Diameter:**

Between 0.069 inches and 0.074 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.138 inches

**Center To Center Distance Between Holes:**

7.350 inches

**First End Taper Length:**

0.030 inches

**Second End Relationship With First End:**

Identical

**Second Shank Diameter:**

Between 0.182 inches and 0.187 inches

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.343 inches

**Product Name:**

Pin, shroud, spacer

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, cl2, ty2 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.