

View Online at <https://aerobasegroup.com/nsn/5315-00-110-5577>

First End Style:

Chamfered

Shank Length:

0.343 inches

Shoulder Diameter:

Between 0.308 inches and 0.312 inches

Shank Diameter:

Between 0.182 inches and 0.187 inches

Overall Length:

7.620 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.069 inches and 0.074 inches

Second Hole Diameter:

Between 0.069 inches and 0.074 inches

Distance From Centerline Of Hole To End Of Pin:

0.138 inches

Center To Center Distance Between Holes:

7.350 inches

First End Taper Length:

0.030 inches

Second End Relationship With First End:

Identical

Second Shank Diameter:

Between 0.182 inches and 0.187 inches

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Second Shank Length:

0.343 inches

Product Name:

Pin, shroud, spacer

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, cl2, ty2 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.