NSN 5315-00-119-7522

First End Style:

Second End Style:

Shoulder Diameter:

Shank Diameter:

Between 0.498 inches and 0.500 inches

Chamfered

Chamfered **Shank Length:**0.375 inches

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-119-7522

Grand Statilotor.
Between 0.370 inches and 0.375 inches
Overall Length:
2.375 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
0.190 inches
Distance From Centerline Of Hole To End Of Pin:
0.187 inches
First End Taper Length:
0.031 inches
Second End Taper Length:
0.125 inches
Second End Relationship With First End:
Not identical
Hardness Rating:
28.0 rockwell c and 30.0 rockwell c
Second Shank Diameter:
Between 0.370 inches and 0.375 inches
First End Location:
Long end
First End Taper Angle:
45.0 degrees
Surface Finish:
63.0 microinches outside diameter
Second End Taper Angle:
15.0 degrees
Second Shank Length:
1.625 inches
Special Features:
Hole tapped 10-24 umc 3b thread and short shank chamfer to have a 0.031 in. Radius
Material:
Steel comp 416

NSN 5315-00-119-7522

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0