NSN 5315-00-126-6150

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-126-6150 **Shank Diameter:** Between 0.3720 inches and 0.3735 inches **Button Handle Diameter:** Between 0.875 inches and 1.135 inches **Detent Quantity: Actuation Method:** Push button **End Application:** W/s: mobile eww support system, an/mlq-36a; aircraft, b-2 bomber (atb); aircraft, hornet f/a-18; support equipment (se), b-2 bomber **Grip Length:** Between 3.300 inches and 3.320 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 20600 double pound **Shoulder To Head End Distance:** 1.040 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 0.365 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator: Button** Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A212a0

Demilitarization:

NSN 5315-00-126-6150

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.