

View Online at <https://aerobasegroup.com/nsn/5315-00-128-6476>

**Head Diameter:**

Between 0.485 inches and 0.515 inches

**Shank Diameter:**

Between 0.3700 inches and 0.3730 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.187 inches

**Detent Quantity:**

2

**Grip Length:**

Between 2.600 inches and 2.620 inches

**Actuation Type:**

Pull and push

**Shoulder To Head End Distance:**

Between 0.380 inches and 0.560 inches

**Detent To Tapered End Distance:**

Between 0.330 inches and 0.390 inches

**Material:**

Steel comp 1109 spindle or steel comp 1110 spindle or steel comp 1116 spindle or steel comp 1117 spindle or steel comp 1118 spindle or steel comp 1119 spindle or steel comp 1132 spindle or steel comp 1137 spindle or steel comp 1139 spindle or steel comp 1140 spindle or steel comp 1141 spindle or steel comp 1144 spindle or steel comp 1145 spindle or steel comp 1146 spindle or steel comp 1151 spindle or steel comp 1211 spindle or steel comp 1212 spindle or steel comp 1213 spindle or steel comp 1215 spindle or steel comp b1111 spindle or steel comp b1112 spindle or steel comp b1113 spindle or steel comp 12114 spindle or steel comp 4130 spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response spindle or mil-c-81562 type 2 cl 2 military specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-c-81562 spec.