

View Online at <https://aerobasegroup.com/nsn/5315-00-128-6476>

Head Diameter:

Between 0.485 inches and 0.515 inches

Shank Diameter:

Between 0.3700 inches and 0.3730 inches

Ring Handle Diameter:

Between 1.000 inches and 1.187 inches

Detent Quantity:

2

Grip Length:

Between 2.600 inches and 2.620 inches

Actuation Type:

Pull and push

Shoulder To Head End Distance:

Between 0.380 inches and 0.560 inches

Detent To Tapered End Distance:

Between 0.330 inches and 0.390 inches

Material:

Steel comp 1109 spindle or steel comp 1110 spindle or steel comp 1116 spindle or steel comp 1117 spindle or steel comp 1118 spindle or steel comp 1119 spindle or steel comp 1132 spindle or steel comp 1137 spindle or steel comp 1139 spindle or steel comp 1140 spindle or steel comp 1141 spindle or steel comp 1144 spindle or steel comp 1145 spindle or steel comp 1146 spindle or steel comp 1151 spindle or steel comp 1211 spindle or steel comp 1212 spindle or steel comp 1213 spindle or steel comp 1215 spindle or steel comp b1111 spindle or steel comp b1112 spindle or steel comp b1113 spindle or steel comp 12114 spindle or steel comp 4130 spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response spindle or mil-c-81562 type 2 cl 2 military specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-c-81562 spec.