

View Online at <https://aerobasegroup.com/nsn/5315-00-133-1096>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.231 inches and 0.250 inches

**Second Hole Diameter:**

Between 0.231 inches and 0.250 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.625 inches

**Center To Center Distance Between Holes:**

Between 5.062 inches and 5.067 inches

**Pinlength:**

6.310 inches

**Pindiameter:**

Between 0.4978 inches and 0.4988 inches

**First End Taper Length:**

0.030 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

88.3 rockwell superficial 15-n and 91.4 rockwell superficial 15-n

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

63.0 microinches outside diameter

**Special Features:**

45 degrees angle between c/l of holes

**Material:**

Steel comp 1015 or steel comp 1025

**Material Specification:**

Qq-s-630 federal specification all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0