

View Online at <https://aerobasegroup.com/nsn/5315-00-138-6136>

First End Style:

Chamfered

Head Style:

Flat fillister

Diameter:

Between 0.1903 inches and 0.1905 inches

Effective Length:

0.567 inches

Undercut Diameter:

Between 0.160 inches and 0.180 inches

Under Head Length:

Between 0.699 inches and 0.719 inches

Undercut Width:

0.025 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.073 inches and 0.083 inches

Distance From Centerline Of Hole To End Of Pin:

0.101 inches

First End Taper Length:

0.020 inches

Grip Length:

Between 0.603 inches and 0.613 inches

Hardness Rating:

44.0 rockwell c and 62.0 rockwell c

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

Between 0.271 inches and 0.291 inches

Surface Finish:

32.0 microinches long shank

Height:

Between 0.104 inches and 0.114 inches

Material:

Steel comp e52100

Material Specification:

Mil-s-7420 military specification single material response or ams6440 assn standard single material response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7420 spec.