

View Online at <https://aerobasegroup.com/nsn/5315-00-138-6136>

**First End Style:**

Chamfered

**Head Style:**

Flat fillister

**Diameter:**

Between 0.1903 inches and 0.1905 inches

**Effective Length:**

0.567 inches

**Undercut Diameter:**

Between 0.160 inches and 0.180 inches

**Under Head Length:**

Between 0.699 inches and 0.719 inches

**Undercut Width:**

0.025 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.073 inches and 0.083 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.101 inches

**First End Taper Length:**

0.020 inches

**Grip Length:**

Between 0.603 inches and 0.613 inches

**Hardness Rating:**

44.0 rockwell c and 62.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

Between 0.271 inches and 0.291 inches

**Surface Finish:**

32.0 microinches long shank

**Height:**

Between 0.104 inches and 0.114 inches

**Material:**

Steel comp e52100

**Material Specification:**

Mil-s-7420 military specification single material response or ams6440 assn standard single material response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-7420 spec.