

View Online at <https://aerobasegroup.com/nsn/5315-00-141-6870>

First End Style:

Chamfered

Second End Style:

Round

Thread Class:

3a

Thread Pitch Diameters:

+0.5264 to 0.5294 inches

Thread Direction:

Right-hand

Thread Length:

0.907 inches

Shank Length:

Between 0.814 inches and 0.843 inches

Shoulder Diameter:

0.828 inches

Shank Diameter:

Between 0.557 inches and 0.562 inches

Overall Length:

1.750 inches

First End Taper Length:

0.047 inches

Thready Qty Per Inch (tpi):

18

Second End Relationship With First End:

Not identical

Thread Size:

0.562 inches

Second Shank Diameter:

Between 0.557 inches and 0.562 inches

First End Location:

Short shank end

First End Taper Angle:

45.0 degrees

Second End Outer Radius:

0.281 inches

Second Shank Length:

Between 0.814 inches and 0.843 inches

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Chromium

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5626 spec.