

View Online at <https://aerobasegroup.com/nsn/5315-00-143-0642>

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.600 inches and 2.620 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

9200 double pounds per square inch

Shoulder To Head End Distance:

0.890 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Special Features:

Steel attaching hook or ring, qq-w-423, comp 302 with passivated surface, qq-p-35

Material:

Steel comp 631 or steel comp 302 spring

Material Specification:

Ams 5673 assn standard 1st material response or qq-w-423, cond b federal specification 2nd material response spring

Surface Treatment:

Anodize or chromate or passivate handle

Surface Treatment Specification:

Mil-a-8625, type 1 military specification 1st treatment response or mil-a-8625, type 2, cl 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response or qq-p-35 federal specification 3rd treatment response button

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.