

View Online at <https://aerobasegroup.com/nsn/5315-00-143-6047>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.120 inches and 0.140 inches

**Second Hole Diameter:**

Between 0.120 inches and 0.140 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.190 inches

**Center To Center Distance Between Holes:**

5.050 inches

**Pinlength:**

5.470 inches

**Pindiameter:**

Between 0.4950 inches and 0.5000 inches

**First End Taper Length:**

0.060 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

58.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Material:**

Steel comp 1010 or steel comp 1025

**Material Specification:**

Qq-s-634 federal specification all material responses

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-c-16232, ty2 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-c-16232 spec.