

View Online at <https://aerobasegroup.com/nsn/5315-00-144-8309>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Button Handle Diameter:**

Between 1.300 inches and 1.400 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.100 inches and 4.120 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c spindle

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.190 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel comp 4130 or stainless steel steel comp 4135 shank

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

Button

**Specification Data:**

80205-nas1338 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.