NSN 5315-00-144-8309

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-144-8309 **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Button Handle Diameter:** Between 1.300 inches and 1.400 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 4.100 inches and 4.120 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c spindle **Shear Strength:** 32800 double pound **Shoulder To Head End Distance:** 1.190 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches Material: Steel comp 4130 or stainless steel steel comp 4135 shank **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator: Button Specification Data:** 80205-nas1338 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A212a0

NSN 5315-00-144-8309

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.