## NSN 5315-00-149-5276

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-149-5276 **Head Diameter:** Between 0.360 inches and 0.450 inches **Shank Diameter:** Between 0.2331 inches and 0.2346 inches **Ring Handle Diameter:** 1.125 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** 1.1811 inches **Actuation Type:** Pull and push **Features Provided:** Lock open feature **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent **Shear Strength:** 8008 double pounds per square inch **Shoulder To Head End Distance:** 0.935 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** Between 0.360 inches and 0.410 inches **Special Features:** Steel attaching link/band, surface treatment cadmium qq-p-416, type 1, cl 3 Material: Steel spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5315-00-149-5276

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.