

View Online at <https://aerobasegroup.com/nsn/5315-00-150-2944>

Head Diameter:

Between 0.530 inches and 0.630 inches

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Ring Handle Diameter:

1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.700 inches and 2.720 inches

Actuation Type:

Pull and push

Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

Shear Strength:

20600 double pounds per square inch

Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.460 inches and 0.510 inches

Material:

Aluminum button or aluminum alloy 2024 button or steel comp 302 button or steel comp 303 button

Material Specification:

Qq-w-423, comp 302, cond b federal specification 1st material response spring and ams 5673 assn standard 2nd material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-37 federal specification single treatment response spring or mil-s-5002 military specification single treatment response spring

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.