NSN 5315-00-150-2944

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-150-2944 **Head Diameter:** Between 0.530 inches and 0.630 inches **Shank Diameter:** Between 0.3720 inches and 0.3735 inches **Ring Handle Diameter:** 1.125 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.700 inches and 2.720 inches **Actuation Type:** Pull and push **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent **Shear Strength:** 20600 double pounds per square inch **Shoulder To Head End Distance:** 1.000 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.460 inches and 0.510 inches Material: Aluminum button or aluminum alloy 2024 button or steel comp 302 button or steel comp 303 button **Material Specification:** Qq-w-423, comp 302, cond b federal specification 1st material response spring and ams 5673 assn standard 2nd material response spring **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-37 federal specification single treatment response spring or mil-s-5002 military specification single treatment response spring **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A212a0

Demilitarization:

NSN 5315-00-150-2944

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.